



## INDUSTRIAL NETWORK SECURITY SYSTEM

## MODEL ELK-NS1120 Series

	<b>KEY FEATURES</b> <ul style="list-style-type: none"><li>▶ 1U rackmount network platform</li><li>▶ Support Intel® Pentium® III (Tualatin) up to 1.4GHz</li><li>▶ Built-in twelve 10/100 Ethernet ports</li><li>▶ One removable 2.5" HDD bay</li><li>▶ On-board Compact Flash socket</li><li>▶ One heatsink for Pentium® III coppermine CPU</li></ul>
	

### DESCRIPTION

1U Rackmount Network Security Appliance with Intel® Pentium® III Processor and 12 Ethernet Ports

### SPECIFICATIONS

Construction	1U rackmount chassis, heavy-duty steel
Dimensions	426(W) x 305(D) x 43.5(H) mm (16.8" x 12" x 1.72")
Processor	Support Intel® Pentium® III (Tualatin) up to 1.4GHz
Chipset	Intel® 815E (B step)
Memory	Max. 512MB SDRAM, 168 pin 25" DIMM socket x 1 Optional onboard SDRAM up to 256MB
Storage	One removable 2.5" HDD bay On-board Compact Flash socket
Cooling System	One Pentium III Coppermine CPU heatsink Two 40mm fans for system cooling
System Control and Indicator	Power LED x 1 Power on/off switch x 1 (rear) Act/ Link, 10/100 LED x 12 on RJ-45
Ethernet	RJ-45 with LED x 12 10/100 Base-TX port x 12 Intel® PRO/100 Network Connection (Intel LAN S82559ER) x 11; Intel® PRO/100 VM Network Connection (Intel LAN S82562EM) x 1
System Console Port	COM port x 1 (rear), RS-232 DB-9 connector USB x 2 (rear)
Expansion	Riser Card: One PCI slot (Optional)
CPU Heatsink	For Tulayen CPU (P/N 5050300093)
Power Supply	180W ATX power supply 90 ~ 264V full range @47 ~ 63 Hz
Color	PANTONE 295U
Environment	Operating temperatures : 0°C to 40°C Storage temperatures : -20°C to 80°C Relative humidity : 10% to 90% (Non-condensing)
Certification	CE FCC

### ORDERING INFORMATION

MODEL	DESCRIPTION
ELK-NS1120L	1U Rack Mount Network System Platform(Intel® Pentium® III (Tualatin) up to 1.4GHz, Built-in twelve 10/100 Ethernet ports, RJ-45 with LED x 12 10/100 Base-TX port x 12 Intel® PRO/100 Network Connection and COM port x 1 (rear), RS-232 DB-9 connector USB x 2 (rear) 180W ATX power supply 90 ~ 264V full range @47 ~ 63 Hz)
ELK-NS1120P	1U Rack Mount Network System Platform(Intel® Pentium® III (Tualatin) up to 1.4GHz, Built-in twelve 10/100 Ethernet ports, RJ-45 with LED x 12 10/100 Base-TX port x 12 Intel® PRO/100 Network Connection and COM port x 1 (rear), RS-232 DB-9 connector USB x 2 (rear) 180W ATX power supply 90 ~ 264V full range @47 ~ 63 Hz)

**WARRANTIES:** 1 Year Return to Factory Warranty

Specifications subject to change without notice.



#128-4, CHEONGPADONG-3GA, YONGSAN-GU, SEOUL, 140-133, KOREA  
PHONE: 82-2-707-0404 FAX: 82-2-716-7690 [www.asanst.com](http://www.asanst.com) E-mail: [elk@asanst.com](mailto:elk@asanst.com)  
ELK is a registered trademark of ASAN ST Co., Ltd.