

	<p>KEY FEATURES</p> <ul style="list-style-type: none"> ▶ Each port individually configurable for RS-422 or RS-485 ▶ 16C554 buffered UARTs with 16-byte FIFOs ▶ Data rates to 460.8K bps ▶ 40-pin right-angle header connector ▶ Extended temperature range available (-40°C - +85°C)
---	--

DESCRIPTION

The ELK-PC3543 PC/104 serial interface provides four serial ports, each individually configurable for RS-422 or RS-485. The board is capable of data rates to 460.8K bps and utilizes a 16C554 UART that provides 16-byte Tx/Rx FIFOs. Ordering options allow the choice of UARTs with larger FIFOs, support for custom baud rates, and 9-bit protocols. The software utilities make installation and operation easy.

SPECIFICATIONS

Number of ports	4
Communications chip	16C554
Max. data rate	460.8K bps
Max. data distance	4000 feet
Operating temperature	0 - +70°C
Storage temperature	-50 - +105°C
Humidity range	10 - 90% R.H.

ORDERING INFORMATION

MODEL	DESCRIPTION
ELK-PC3543	PC/104 RS-422/485 Serial Interface
ELK-PC3543-SE	PC/104 RS-422, RS-485 Serial Interface With 16C854 UART
ELK-PC3543-SN	PC/104 RS-422, RS-485 Serial Interface With 16C954 UART
ELK-CA273	40-Pin IDC Ribbon Cable to (4) DB9 Male Connectors, 14" in Length
ELK-CA110	DB37 Male to IDC40 Ribbon Cable 6" in Length
ELK-CA143	DB37 Female to (4) DB9 Male, 36" in Length - for 7402, 7404, 7904, 3440, etc.
ELK-CA222	IDC40 to IDC40 Ribbon Cable, 18" in Length
ELK-CA190	DB9 Female to DB9 Female, 72" in Length - RS-422 207M SMPTE Cable)
ELK-DB103	Converts DB9 Male RS-422 to Opto 22 Optomux Compatible DB9 Female
ELK-TB10	Terminal Block - IDC40 to (4) DB9 Male Connectors - for 354x Multi-Port Interface Adapters
ELK-TB02-KT	Terminal Block Kit - DB37 Male and DB37 Female to 37 Screw Terminals

All Specifications within this document are subject to change without notice.



RM309, Woolim e-BIZ Center, #16 Yangpyeongdong-3Ga, Yeongdeungpo-Gu, Seoul, 150-946, Korea
 Phone : 82-2-2164-9933 Fax : 82-2-2164-9229 www.asanst.com E-mail: elk@asanst.com
 ELK is a registered trademark of ASAN ST Co., Ltd.